



► A range of robust, enduring systems that stand up to the heavy duty nature of...

AUTOMOTIVE ENVIRONMENTS

Welcome to Flowcrete Australia

Flowcrete Australia offers an exclusive range of high performance industrial formulations designed to combine superior resistance with exceptional durability, delivering reliable floor finishes for heavy duty environments.

Flowcrete Australia understands that the automotive sector is tough and demanding. We have developed a range of robust, enduring systems that stand up to sustained vehicular and pedestrian traffic, whilst boasting impressive resistance to commonplace workshop chemicals such as battery acids, petrol, antifreeze and brake fluid.


What's more, our seamless, brightly coloured resins allow for demarcation, colour zoning, coving and drainage whilst offering tailored slip resistance through broadcasting aggregates into the mix, allowing for the numerous practicalities of these environments.

Automotive Environments Floor Plan



- | | | | |
|--|---|---|--|
| 1 External Driveways
Deckshield ID
Deckshield ID Rapide | 3 Offices
Mondéco EP
Mondéco Rapide | 5 Consultation Rooms
Mondéco EP
Mondéco Rapide | 7 Service Workshops
Flowcoat UV
Flowcrete SR |
| 2 Internal Showrooms
Rustik + UV
Mondéco Rapide | 4 Lounge Areas
Mondéco EP
Mondéco Rapide | 6 Amenities
Flowfast Terrosso
Flowfast SRQ | 8 Wash Areas
Deckshield ID
Deckshield ID Rapide |


✓ For the application suitability of each system, look out for the check mark symbol throughout the brochure.



Flowcoat OP (0.3–1.5 mm)

A high performance, solvent free, epoxy resin coating system designed to create an “Orange Peel” surface texture. This system can be lightly or fully textured to provide a non-slip finish making it ideal for use within vehicle workshops. Smooth, light and full non-slip finishes are available.

☒ VEHICLE WORKSHOPS



FIRE RESISTANCE

CHF Value	kW/m ²
Smoke Value	5% (Mean)

SLIP RESISTANCE

Method described in AS4586-2013	Dry & Wet Rating is dependant on specification (In accordance with AS4586-2013)
---------------------------------	---

BOND STRENGTH

ASTM D4541 (Pull-Off Test)	> 1.5MPa*
----------------------------	-----------

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.






Flowshield OP (2.5–4 mm)

A high performance, solvent free, chemical resistant, high-build epoxy resin coating system. Typically used as a hard wearing coloured floor coating in areas such as vehicle workshops and wash bays. Smooth, light and full non-slip finishes are available.

☒ VEHICLE WORKSHOPS, TRUCK WORKSHOPS, WASH BAYS



FIRE RESISTANCE

EN 13505-1

B_{fl}-s1

SLIP RESISTANCE

Method described in AS4586-2013

Dry & Wet Rating is dependant on specification (In accordance with AS4586-2013)

ABRASION RESISTANCE

Taber Abrader 1kg load using CS17 wheels


90 mg loss per 1000 cycles

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.

Flowcoat UV (0.35–1.5 mm)

A high performance, hard-wearing, coloured epoxy and polyurethane resin coating system. Typically used as a hard wearing, protective coating for areas where a combination of chemical resistance, durability, UV resistance and abrasion resistance is required. Smooth, light and full non-slip finishes are available.

✓ VEHICLE WORKSHOPS



FIRE RESISTANCE - AS/ISO 9239.1

CHF Value	- kW/m ²
Smoke Value	4% (Mean)

WATER PERMEABILITY

Karsten Test	Nil (Impermeable)
--------------	-------------------

SURFACE HARDNESS

Koenig Hardness Test	180 secs
----------------------	----------




Flowshield UV (2.5–4 mm)

A durable, high performance, chemical and UV resistant resin flooring solution designed to provide added impact protection in industrial environments. Typically used to provide a textured platform for industrial areas exposed to UV. Smooth, light and full non-slip finishes are available.

✓ VEHICLE WORKSHOPS, TRUCK WORKSHOPS, WASH BAYS

FIRE RESISTANCE	
EN 13505-1	B _{fl} -s1
COMPRESSIVE STRENGTH	
BS6319	> 50 N/mm ²
ABRASION RESISTANCE	
Taber Abrader 1kg load using CS17 wheels	90 mg loss per 1000 cycles




Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.

Flowcrete SR (4–6 mm)

A durable, chemical resistant polyurethane resin system featuring a positively textured semi-gloss finish. Typically used in workshops, factories, warehousing, distribution, manufacturing facilities and chemical processing plants.

✓ VEHICLE WORKSHOPS, TRUCK WORKSHOPS, WASH BAYS



FIRE RESISTANCE - AS/ISO 9239.1

CHF Value	10 kW/m ²
Smoke Value	69% (Mean)

WATER PERMEABILITY

Karsten Test	Nil (Impermeable)
--------------	-------------------

IMPACT RESISTANCE

EN ISO 6272	15Nm
-------------	------


Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



Deckshield ID (1.5 mm)

A low VOC, flexible polyurethane deck coating system that transforms internal parking structures. Typically used to cosmetically enhance, reduce noise, protect and brighten internal car parks.

EXTERNAL DISPLAY AREAS, CAR PARKS & RAMPS



FIRE RESISTANCE	
EN 13505-1	B _{fl} -s1
WATER PERMIABILITY	
Karsten Test	Nil (Impermeable)
ABRASION RESISTANCE	
Taber Abrader1kg load using CS17 wheels	90 mg loss per 1000 cycles




Deckshield ED Rapide (4 mm)

A flexible MMA car park deck coating providing a colourful, watertight, durable surface for exposed decks. Typically used to cosmetically enhance and protect external display areas and car parks.

EXTERNAL DISPLAY AREAS, CAR PARKS & RAMPS

WATER PERMEABILITY	
Karsten Test	Nil (Impermeable)
CRACK BRIDGING	
BS EN 1062-7 Method A Table 6	Class A3 (-20°C)
SPEED OF CURE	PER COAT
Walk On	1 hr
Full Traffic & Chemical Cure	2 – 3 hrs




Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



Mondéco Rapide (8 mm)

An innovative, rapid curing, seamless, resin-based decorative terrazzo floor finish which features white marble aggregates. Typically used in high-end vehicle showrooms. Its quick curing properties reduce downtime during installation.

☒ VEHICLE SHOWROOMS



WEAR RESISTANCE

EN 13892-4	Max. wear depth < 5µm
------------	-----------------------

IMPACT RESISTANCE

ISO 6272-1	10 Nm
------------	-------

SPEED OF CURE


Light Traffic	1 hr
Full Traffic	2 – 3 hrs
Full Chemical Cure	2 – 3 hrs

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.

Mondéco EP (8 mm)

A low odour, seamless resin-based decorative terrazzo floor finish which features white marble aggregates. It's highly durable finish provides a long life cycle solution.

✓ VEHICLE SHOWROOMS



FIRE RESISTANCE - AS/ISO 9239.1

CHF Value	- 9.5 kW/m ²
Smoke Value	266% (Mean)

FLEXURAL STRENGTH

EN 13892-2	>20 N/mm ²
------------	-----------------------

TEMPRETURE RESISTANCE

Tolerant of sustained temperatures up to 60°	
--	--


Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.



Rustik + UV (6 mm)

A stone carpet system that uses colourful stone aggregates bound with a clear resin to provide a natural looking interior floor finish. Suitable for car showrooms, retail stores, reception halls and commercial spaces.

☒ VEHICLE SHOWROOMS



THERMAL RESISTANCE

Tolerant up to 60°C

ABRASION RESISTANCE


BS8204:PART 2:2002	Class AR2 – Medium duty industrial and commercial
--------------------	---

COMPRESSIVE STRENGTH

BS 6319	30 N/mm ²
---------	----------------------

Applied colours may differ from the examples shown. For a full technical profile, colour chart and samples, contact your local Flowcrete office.





Flowcrete

World leader in seamless resin flooring solutions and other specialist coatings.

Africa

South Africa	+27 31 701 0017	southafrica@flowcrete.com
--------------	-----------------	---------------------------

Asia Pacific (APAC)

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+603 6277 9575	bangladesh@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Korea	+60 3 6277 9575	korea@flowcrete.com
Malaysia	+60 3 6277 9575	asia@flowcrete.com
New Zealand	+64 7 541 1221	newzealand@flowcrete.com
Pakistan	+60 3 6277 9575	pakistan@flowcrete.com
Philippines	+63 2 834 6506	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Taiwan	+60 3 6277 9575	taiwan@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 28 6287 0846	vietnam@flowcrete.com

Europe & Middle East (EME)

Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 6486 0830	norway@flowcrete.com
Poland	+48 22 879 8907	poland@flowcrete.com
Romania	+40 766 596 991	romania@flowcrete.com
Russia	+7 916 931 3513	russia@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 2946570	turkey@flowcrete.com
UAE	+971 4 347 0460	uae@flowcrete.com
UK	+44 (0) 1270 753 000	uk@flowcrete.com

India

India	+91 44 40176600	india@flowcrete.com
-------	-----------------	---------------------

North America

Canada	+1 877-210-2444	canada@flowcrete.com
Mexico	+55 44 40 94 00	mexico@flowcrete.com
USA	+1 513-943-4225	americas@flowcrete.com