

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Flowfresh Coating Satin - Filler C

Recommended use: Component of multicomponent industrial coatings - Industrial use

Supplier: Tremco CPG Australia Pty Ltd

ABN: 25 000 024 064

Street Address: 12/4 Southridge Street

Eastern Creek NSW 2766

Telephone: 02 9638 2755 **Facsimile:** 02 9638 2955

Emergency Telephone number: 02 9037 2994

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.







Signal Word

Danger

Hazard Classifications

Skin Corrosion/Irritation - Category 2 Eye Damage/Irritation - Category 1 Sensitisation - Skin - Category 1 Carcinogenicity - Category 1A

Specific Target Organ Toxicity (Single Exposure) - Category 2 Specific Target Organ Toxicity (Repeated Exposure) - Category 2

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H350	May cause cancer .
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

Prevention Precautionary Statements

P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust, fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing including eye/face protection.
P284	In case of inadequate ventilation wear respiratory protection.

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108

Issued: 2022-03-23 Version: 2 Page 1 of 7



Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor (insert appropriate source

of emergency medical advice).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor/insert appropriate source of emergency

medical advice.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse

Storage Precautionary Statement

P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule:

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Cement, portland, chemicals Calcium hydroxide (Ca(OH)2) Iron oxide (Fe2O3) Sulfuric acid, calcium salt (1:1) Calcium oxide Limestone Quartz (SiO2) Ingredients determined to be Non-Hazardous	65997-15-1 1305-62-0 1309-37-1 7778-18-9 1305-78-8 1317-65-3 14808-60-7	50-75 % 10-25 % 2.5-10 % 2.5-10 % 2.5-10 % 1.0-2.5 % Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Move to fresh air. Consult a physician after significant exposure.

Skin Contact: Use a mild soap if available. Wash off with soap and plenty of water.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses. If eye irritation persists, consult a specialist.

Ingestion: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108 Issued: 2022-03-23 Version: 2 Page 2 of 7



Page 3 of 7

PPE for First Aiders: Wear overalls, gloves, safety glasses, dust mask. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or reusing.

Notes to physician: Treat symptomatically. Effects may be delayed. Can cause corneal burns. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.4.2 Most important symptoms and effects, both acute and delayed. Harmful by inhalation.4.3 Indication of any immediate medical attention and special treatment needed. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water.

LARGE SPILLS

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Avoid dust formation. Protect from moisture.

Storage: Keep tightly closed in a dry and cool place

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

Issued: 2022-03-23

	TWA		STEL	NOTICES
ppm	mg/m3	ppm	mg/m3	

Calcium hydroxide - 5 - - -

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108

Version: 2



Calcium oxide	-	2	-	-	-
Calcium sulphate	-	10	-	-	-
Iron oxide fume (Fe2O3) (as Fe)	-	5	-	-	-
Portland cement	-	10	-	-	-
Quartz (respirable dust)	-	0.05	-	-	Carc. 1A
Silica Crystalline - Quartz (respirable dust)	-	0.05	-	-	Carc. 1A

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: OVERALLS, GLOVES, SAFETY GLASSES, DUST MASK.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear overalls, gloves, safety glasses, dust mask. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

RESPIRATORY PROTECTION: Effective dust mask.EYE PROTECTION: Safety glasses with side-shields.HAND PROTECTION: Protective gloves. Long sleeved clothing. Remove and wash contaminated clothing before reuse.OTHER PROTECTIVE EQUIPMENT: No InformationENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas

Hygiene measures: Wash hands before breaks and at the end of workday. Do not breathe dust. When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Base Units: Kilogram Form: Powder Odour: Slight

Solubility: Not determined Not Determined

Specific Gravity: 0.092
Density: ~1.03

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108

Issued: 2022-03-23 Version: 2 Page 4 of 7



Page 5 of 7

Relative Vapour Density (air=1): Not determined Vapour Pressure (20 °C): Not determined

Flash Point (°C): 999

Flammability Limits (%): Not determined **Autoignition Temperature (°C):** Not determined Melting Point/Range (°C): Not determined Pour Point/Range (°C): Not determined **Boiling Point/Range (°C):** N.D. - N.D **Decomposition Point (°C):** Not determined Sublimation Point (°C): Not determined **Dropping Point (°C):** Not determined :Hq Not Determined Viscosity: Not Determined **Surface Tension:** Not Determined Evaporation Rate (n-Butyl acetate=1): Not Determined **Partition Coefficient:** Not Determined

Total VOC (g/Litre): 0

Odour Threshold:

Explosive properties:

Oxidising properties:

Volatile by Volume:

Molecular Formula:

Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Conditions to avoid: No Information

Incompatible materials: Do not store near acids. Strong oxidizing agents.

Hazardous decomposition products: No hazardous decomposition products are known. Hydrogen fluoride

Hazardous reactions: No reactivity hazards known under normal storage and use conditions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

Skin contact: No Information A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: No Information

Eye contact: No Information Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108

Issued: 2022-03-23 Version: 2



Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 5.0$ mg/L for dust.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Calcium hydroxide LD50 (Rat): 340 mg/kr (Method: Oral) Red Iron Oxide LD50 (Rat): >2000 mg/kg (Method: Oral)

Quartz (Silicon Dioxide) LD50 (Rat): >2000 mg/kg (Method: Oral)

Corrosion/Irritancy: Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as a Category 2 Hazard.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as a Category 1A Hazard.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 2 Hazard.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information

Long-term aquatic hazard: No information

Ecotoxicity: No information

Persistence and degradability: No information

Bioaccumulative potential: No information

Mobility: No information

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108

Issued: 2022-03-23 Version: 2 Page 6 of 7



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): .

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Flowfresh Coating Satin - Filler C Reference No: B1CMY600108