

Architectural Specification

Project Name:

System Name:

Flowfast Kristalina

Description: Flowfast Kristalina is a seamless, decorative, hard-wearing, methyl

methacrylate resin floor finish.

Thickness: 1.5 - 2mm

Colour:

Slip Resistant Rating:

Finish: Matte

Preamble: This specification assumes a concrete base >25 N/mm² compressive

strength, application temperature 10-25°C, presence of an effective damp proof membrane and moisture content below 75% RH in the

concrete. If above 75% RH contact Flowcrete Australia.

Surface Preparation: Enclosed shotblasting or course diamond grinding of concrete to remove

any surface contaminants. Edges completed by vacuum controlled hand tools. All residues must be removed to provide a dry and dust free open

textured surface.

Curing: 1 Hour Cure at 25°C.

Traffic: Full traffic after 2 hours at 25°C.

Note: Coving forms an integral part of the flooring system. It creates a sealed

finish between the floor and wall joint. Please refer to Flowtex F1

Coving Mortar for further information.

Products included in system

Email: australia@flowcrete.com

Flowfast Standard Primer

Anti Slip Aggregate

• Flowfast Standard Binder

Kristalina Flakes

Flowfast Standard Sealer

Cleaning: Please consult our Technical Advisory team 07 3205 7115 or email

australia@flowcrete.com for specific cleaning and maintenance

requirements.

Additional information Please consult product Health & Safety, system, product and

application data or contact our Technical Advisory team 07 3205 7115 or

email australia@flowcrete.com

Any recommendation or suggestion relating to the use of the products made by Flowcrete Australia Pty Ltd., whether in its technical literature, or in response to a specific enquiry, or otherwise, is based upon data believed to be reliable, however the products and information are intended for use by customers having requisite skill and know-how in the industry and therefore it is for the customer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that the customer has done so at its sole discretion and risk.