

# Safety Data Sheet

## Hazardous, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Flowfast Flexible Sealer E**

Recommended use: Topcoat

**Supplier:** Tremco CPG Australia Pty Ltd  
**ABN:** 25 000 024 064  
**Street Address:** 12/4 Southridge Street  
Eastern Creek NSW 2766  
**Telephone:** 02 9638 2755  
**Facsimile:** 02 9638 2955

Emergency Telephone number: **02 9037 2994**

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.



**Signal Word**  
Danger

#### Hazard Classifications

Flammable Liquids - Category 2  
Acute Toxicity - Oral - Category 4  
Skin Corrosion/Irritation - Category 2  
Sensitisation - Skin - Category 1  
Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation  
Chronic Hazard to the Aquatic Environment - Category 3

#### Hazard Statements

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

#### Prevention Precautionary Statements

P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..  
P264 Wash hands, face and all exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.

# Safety Data Sheet



- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing including eye/face protection.

### Response Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.
- P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P330 Rinse mouth.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse
- P370+P378 In case of fire: Use (insert appropriate media) to extinguish.

### Storage Precautionary Statements

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

### Disposal Precautionary Statement

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

### Poison Schedule:

### DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Dangerous Goods Class:** 3

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	50-75 %
2-ETHYLHEXYL ACRYLATE	103-11-7	10-25 %
1,4-BUTANEDIOL DIMETHACRYLATE	2082-81-7	1-2.5 %
1,1'-(P-TOLYLIMINO)DIPRO PAN-2-OL	38668-48-3	1-2.5 %
2-(2H-BENZOTRIAZOL-2-Y L)-P-CRESOL	2440-22-4	<1 %
Ingredients determined to be Non-Hazardous		Balance
		100%

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Move to fresh air. Keep respiratory tract clear. If unconscious place in recovery position and seek medical advice. If not breathing, give artificial respiration. Call a physician if irritation develops or persists.

**Skin Contact:** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician if irritation develops or persists.

# Safety Data Sheet



**Eye contact:** Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

**Ingestion:** Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention immediately.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from butyl rubber, nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically. Effects may be delayed. Move out of dangerous area. Take off all contaminated clothing immediately. Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3YE

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13). Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment.

### LARGE SPILLS

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13). Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment.

**Dangerous Goods - Initial Emergency Response Guide No:** 14

## 7. HANDLING AND STORAGE

# Safety Data Sheet



**Handling:** Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Provide exhaust ventilation close to floor level. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Open drum carefully as content may be under pressure. Use only in well-ventilated areas. Vapours may form explosive mixtures with air. Keep product and empty container away from heat and sources of ignition. Take measures to prevent the build up of electrostatic charge. Do not use sparking tools. Use only explosion-proof equipment. Have fire extinguishers ready before opening the drum.

**Storage:** Store in original container. Never fill containers more than 80 % because aerial oxygen is necessary for stabilising. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep in an area equipped with solvent resistant flooring. Do not store together with oxidizing and self-igniting products.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Methyl methacrylate	50	208	100	416	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from butyl rubber, nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated

# Safety Data Sheet

clothing and other protective equipment before storing or re-using.

## RECOMMENDATIONS FOR CONSUMER USE:

**RESPIRATORY PROTECTION:** Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 141) during spraying operations: Gas filter type A1 (organic substances). Dust filter P3 (for fine dust). **EYE PROTECTION:** If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles. **HAND PROTECTION:** Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of achemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. **OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Keep working clothes separately.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Base Units:** Kilogram  
**Form:** Liquid  
**Colour:** Violet  
**Odour:** acrylic-like

<b>Solubility:</b>	Insoluble in water
<b>Solubility in water:</b>	Insoluble
<b>Specific Gravity:</b>	No information available
<b>Density:</b>	0.99 g/cm <sup>3</sup> (25 °C)
<b>Vapour Pressure (20 °C):</b>	38.7 mbar (MMA)
<b>Flash Point (°C):</b>	12 °C (MMA) / 54 °F
<b>Flammability Limits (%):</b>	No information available
<b>Autoignition Temperature (°C):</b>	No information available
<b>Melting Point/Range (°C):</b>	-48 °C (MMA) / -54 °F
<b>Boiling Point/Range (°C):</b>	101 °C (MMA) / 214 °F
<b>Decomposition Point (°C):</b>	No information available
<b>pH:</b>	No information available
<b>Viscosity:</b>	160 - 200 mPa.s @ 25°C
<b>Evaporation Rate (n-Butyl acetate=1):</b>	No information available
<b>Partition Coefficient:</b>	No information available
<b>Total VOC (g/Litre):</b>	No information available
<b>Explosive properties:</b>	Upper explosion limit 12.5 Vol.% (MMA) Lower explosion limit 2.1 Vol.% (MMA)
<b>Oxidising properties:</b>	No information available

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions

**Conditions to avoid:** Heat, flames and sparks. Exposure to sunlight.

**Incompatible materials:** Avoid radical-forming starting agents, peroxides and reactive metals, Amines, Heavy metal compounds, Oxidizing agents, Reducing agents

**Hazardous decomposition products:** No hazardous decomposition products are known

**Hazardous reactions:** Polymerisation occurs when exposed to white light, ultraviolet light or heat. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers. Polymerisation occurs when exposed to white light, ultraviolet light or heat. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Irritating to mucous membranes. May cause respiratory irritation.

**Skin contact:** Causes skin irritation. May cause an allergic skin reaction. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Ingestion:** Harmful if swallowed. Harmful if swallowed.

**Eye contact:** There are no data available for this product

### Acute toxicity

**Inhalation:** This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients):  $LC_{50} > 20.0$  mg/L for vapours or  $LC_{50} > 5.0$  mg/L for dust and mist.

Methyl methacrylate  $LC_{50}$  (Rat): 29.8 mg/l

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000$  mg/Kg bw

Methyl methacrylate  $LD_{50}$  (Rabbit):  $> 5000$  mg/kg (Method: Dermal)

2-ETHYLHEXYL ACRYLATE  $LD_{50}$  (Rabbit): = 7522 mg/kg (Method: Dermal)

**Ingestion:** This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients):  $300 < LD_{50} \leq 2,000$  mg/Kg bw

Methyl methacrylate  $LD_{50}$  (Rat):  $> 5000$  mg/kg (Method: Oral)

2-ETHYLHEXYL ACRYLATE  $LD_{50}$  (Rat): 4435 mg/kg (Method: Oral)

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

**Aspiration hazard:** This material has been classified as not an aspiration hazard.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

### Chronic Toxicity

**Mutagenicity:** This material has been classified as not a mutagen.

**Carcinogenicity:** This material has been classified as not a carcinogen.



# Safety Data Sheet



**Reproductive toxicity (including via lactation):** This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as not a specific hazard to target organs by repeat exposure.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Methyl methacrylate 48hr EC50 (Daphnia magna): 69 mg/L  
2-ETHYLHEXYL ACRYLATE 48hr EC50 (Daphnia magna): 17.45 mg/L  
2-ETHYLHEXYL ACRYLATE 72hr EC50 (algae): 44 mg/L  
2-ETHYLHEXYL ACRYLATE 96hr EC50 (algae): 47 mg/L  
Methyl methacrylate 96hr EC50 (algae): 170 mg/L  
Methyl methacrylate 96hr LC50 (bluegill sunfish): 170 - 206 mg/L flow-through  
Methyl methacrylate 96hr LC50 (bluegill sunfish): 153.9 - 341.8 mg/L static  
Methyl methacrylate 96hr LC50 (fathead minnow): 243 - 275 mg/L flow-through  
Methyl methacrylate 96hr LC50 (fathead minnow): 125.5 - 190.7 mg/L static  
Methyl methacrylate 96hr LC50 (fish): 326.4 - 426.9 mg/L static  
Methyl methacrylate 96hr LC50 (rainbow trout): 79 mg/L flow-through  
Methyl methacrylate 96hr LC50 (rainbow trout): 79 mg/L static

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF  $\geq$  500 and/or log  $K_{ow} \geq$  4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** The product is partially biodegradable.

**Bioaccumulative potential:** Chemical Name: METHYL METHACRYLATE log Pow: 0.7  
Chemical Name: 2-ETHYLHEXYL ACRYLATE log Pow: 4.64

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

# Safety Data Sheet



**UN No:** 1866  
**Dangerous Goods Class:** 3  
**Packing Group:** II  
**Hazchem Code:** •3YE  
**Emergency Response Guide No:** 14  
**Limited Quantities** 5 L

**Proper Shipping Name:** RESIN SOLUTION

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



**UN No:** 1866  
**Dangerous Goods Class:** 3  
**Packing Group:** II

**Proper Shipping Name:** RESIN SOLUTION

## AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



**UN No:** 1866  
**Dangerous Goods Class:** 3  
**Packing Group:** II

**Proper Shipping Name:** RESIN SOLUTION

## 15. REGULATORY INFORMATION

**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)  
Basel Convention (Hazardous Waste)



# Safety Data Sheet



International Convention for the Prevention of Pollution from Ships (MARPOL)

**This material/constituent(s) is covered by the following requirements:**

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): .

## 16. OTHER INFORMATION

Reason for issue: Product name change

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.